



# Confidence Even Under Fire

# Through-Penetration

## Mortar

### 3M™ Fire Barrier Mortar






Lightweight, endothermic firestop that is ready for mixing with potable water. Firestops penetrations passing through fire-rated floor or wall assemblies.\*

- Up to 3-hour fire ratings per ASTM E 814 (UL 1479)
- Variable mix ratio permits self-leveling as well as trowelable application consistencies
- UL listed systems (including concrete floors with 2-1/2 in. minimum thickness)
- Excellent adhesion — bonds to concrete, metals, wood, plastic and cable jacketing
- Re-enterable/repairable with common trade tools
- Acts as a heat sink, reducing the likelihood of combustible matter igniting on the unexposed side of the assembly
- Dry mix available in 5 gallon (28 lbs.) pails and 44 pound bags

\*Not load bearing.



### 3M™ Fire Barrier Mortar

Product	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
<b>Mortar (non load-bearing)</b> 	Dry Mix Mortar Firestop (Up to 3-hr Penetration Firestop)	28 lbs.		 Pail	000-51115-54901-4	1/Cs	Each
	Dry Mix Mortar Firestop (Up to 3-hr Penetration Firestop)	44 lbs.		 Bag	000-51115-54900-7	1/Cs	Each

### Energy Conservation Technologies

Unit 1 / 251 Ferntree Gully Road  
Mount Waverley Vic 3149

Phone 1300 742 296

Email [enquires@energycontech.com](mailto:enquires@energycontech.com)

Web [www.energycontech.com](http://www.energycontech.com)